

## BLACK MATT SPRAY SOLL (S700001)

Page 1/1

## **Product information**

professional remaining	
Description and application: Product benefits:	<ul> <li>Black matt spray paint is used for repairing cars with minor and medium paint damage. Also as a protective coating for objects of all kinds in the home and garden.</li> <li>Before usage, clean and sand down surface, remove any rust. Apply anti-corrosion primer to clean surface. Then apply primer filler. Shake can well for 2 minutes. Test spray to check compatibility and colour tone. Spraying distance approx. 25 cm.</li> <li>Do not spray on surfaces coated with synthetic resins as the paint may lift.</li> </ul>
	High level of solid matter.
	Very economic.
	Rapid tack-drying and good drying properties.
	Scratch resistant.
	Light-fast and weather resistant.
	Free of heavy metals: no lead, cadmium, chrome.
Binding agent base:	Nitro combination paint.
Spraying coating:	For 2 cross-coats: approx. 40-50 µm.
Drying times:	Dust dry: after approx. 5 - 10 min.
	Dry hard: after approx. 24 hours
Can be painted over:	With itself: at any time.
Paints structure:	Spray directly onto pre-primed surfaces.
Storage and shelf life:	Protect from sunlight and do not expose to temperature exceeding +50°C. We
	guarantee shelf life and quality of the product not less than 3 years.
Packaging:	500 ml
Colour:	Black
Notes:	Turn the can around after use and spray the valve until it is empty.
	I n purpose only. To our knowledge the data provided complies with the latest standard and is based on years of in the manufacture of our products. However the data is not binding and without warranty.