

Product information

Description and application:	This primer creates a smooth surface, an ideal base for a subsequent covering coat, fills small irregularities; it can be applied on any surface and easy to sand down. Suitable for metal, ceramics, stone, clay, glass, paper and some plastics. Before usage, clean and sand down surface, remove any rust. First the surface should be coated with anti-corrosion primer. Shake can well for 2 minutes. Test spray to check compatibility and colour tone. Spraying distance approx. 25 cm. Do not spray on surfaces coated with synthetic resins as the paint may lift.
Product benefits:	Ensures a smooth base. Even top coat. Good adhesion. High filling capacity. Very easy running. Fast drying. Easy to sand down. Free of heavy metals: no lead, cadmium, chrome.
Binding agent base:	Nitro combination resins.
Spraying coating:	For 2 cross-coats: 50-60 µm.
Drying times:	Dust dry: after approx. 20 min. Dry hard: after 12 hours.
Can be painted over:	With itself: at any time.
Paints structure:	1. Anti-corrosion primer. 2. Universal primer. 3. Top coat.
Storage:	Protect from sunlight and do not expose to temperature exceeding +50 °C. We guarantee shelf life and quality of the product not less than 3 years.
Packaging:	500 ml
Colour:	White, grey, black
Notes:	Turn the can around after use and spray the valve until it is empty.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty.