

Product information

Description and application:	Fast drying lacquer to embellish steel and light metal rims and hubcaps. Before usage, clean and sand down surface, remove any rust. Apply anti-corrosion primer to clean surface. Then apply primer filler. Shake can well for 2 minutes. Test spray to check compatibility and colour tone. Spraying distance approx. 25 cm.
Product benefits:	High covering properties. Resistant to road salt, stonechips etc. Wear resistant. Carwash resistant. Free of heavy metals: no lead, cadmium, chrome.
Binding agent base:	Alkyd resins, oil-modified (synthetic resin paint).
Spraying coating:	For 2 cross-coats: 50-60 µm.
Drying times:	Dust dry: after approx. 10 min. Fast to handling: after 2-3 hours. Dry hard: after 12 hours.
Can be painted over:	With itself: within 6 hours.
Paints structure:	1. Anti-corrosion primer. 2. Universal primer. 3. Wheel spray.
Storage:	Protect from sunlight and do not expose to temperature exceeding +50°C. We guarantee shelf life and quality of the product not less than 3 years.
Packaging:	500 ml
Colour:	Silver
Notes:	Turn the can around after use and spray the valve until it is empty.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty.