

WHITE GLOSS SPRAY SOLL (S700009)

Page 1/1

Product information

Description and application:	White gloss spray paint is used for repairing cars with minor and medium paint
	damage. Also as a protective coating for objects of all kinds in the home and garden.
	Before usage, clean and sand down surface, remove any rust. Apply anti-corrosion
	primer to clean surface. Then apply primer filler. Shake can well for 2 minutes. Test
	spray to check compatibility and colour tone. Spraying distance approx. 25 cm.
	Do not spray on surfaces coated with synthetic resins as the paint may lift.
Product benefits:	Easy running.
	High level of solid matter.
	Very economic.
	Rapid tack-drying and good drying properties.
	Scratch resistant.
	Light-fast and weather resistant.
	Free of heavy metals: no lead, cadmium, chrome.
Binding agent base:	Nitro combination paint.
Spraying coating:	For 2 cross-coats: approx. 40-50 μm.
Drying times:	Dust dry: after approx. 5 - 10 min.
	Dry hard: after approx. 24 hours
Can be painted over:	With itself: at any time.
Paints structure:	Spray directly onto pre-primed surfaces.
Storage and shelf life:	Protect from sunlight and do not expose to temperature exceeding +50°C. We
-	guarantee shelf life and quality of the product not less than 3 years.
Packaging:	500 ml
Colour:	White

experience in the manufacture of our products. However the data is not binding and without warranty.