

**Product information**

<b>Description and application:</b>	Spray putty equalises and closes areas of unevenness, scratches and marks on the car; ensures a pore-free surface. Clean and sand down surface, remove any rust. Apply a first coat of anti-corrosion primer. Shake can well for 2 minutes. Test spray to check compatibility and colour tone. Spraying distance approx. 25 cm. When filler is thoroughly dry, sand down with a wet paper grain 600. Do not spray on surfaces coated with synthetic resins as the paint may lift.
<b>Product benefits:</b>	Easy running. High level of solid matter. Very economic. Rapid tack-drying. Good drying properties. Free of heavy metals: no lead, cadmium, chrome.
<b>Binding agent base:</b>	Nitro combination resin.
<b>Spraying coating:</b>	For 2 cross-coats: 40-50 µm.
<b>Drying times:</b>	Dust dry: after 5-10 min. Fast to handling: after 30-40 min. Dry hard: after approx. 24 hours.
<b>Can be painted over:</b>	With itself: at any time.
<b>Paints structure:</b>	1. Anti-corrosion primer or zinc chromate primer. 2. Filler spray. 3. Top coat.
<b>Storage:</b>	Protect from sunlight and do not expose to temperature exceeding +50°C. We guarantee shelf life and quality of the product not less than 3 years.
<b>Packaging:</b>	400 ml
<b>Colour:</b>	Grey
<b>Notes:</b>	Turn the can around after use and spray the valve until it is empty.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty.