

**Product information**

<b>Description and application:</b>	Universal prefilled spray is pre-filled with propeling and other additives. The end product is achieved by adding the paint. Before usage, clean and sand down surface carefully, remove any rust if necessary, apply priemer. Shake can very well. Rest spray to check compatibility and colour tone; minor colour deviations are possible. Spray in an even crossways motion at approx. 20 - 30 cm distance. Drying time depends on type of paint, coat thickness and temperature.
<b>Product benefits:</b>	Suitable for all commercially available synthetic resins, synthetic, nitro-cellulose and acrylic clearcoats.
<b>Drying times:</b>	Dust dry: depending on the product. Fast to handling: depending on the product. Dry hard: depending on the product.
<b>VOC directions:</b>	EC limiting value for the product (cat. B/e): 840 g/l (2007). This product contains max. 840 g/l.
<b>Storage:</b>	Protect from sunlight and do not expose to temperature exceeding +50°C. We guarantee shelf life and quality of the product not less than 3 years.
<b>Packaging:</b>	400 ml
<b>Working conditions:</b>	From +10°C and up to 70 % relative air humidity.
<b>Color:</b>	Depending on the specifications of the product, which has been filled in.
<b>Remarks:</b>	Turn the can around after use and spray the valve until it is empty.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty.