

Technical Information

EU-GB

SOLL SILICON REMOVER

Art.Nr. S700024



Aerosol formulation made for this specific product for easy application
constant atomisation pressure
finest aerosol distribution,
professional paint result

PRODUCT

- easy application
- removes silicone, grease, oil, wax, dirt, tar, grime
- mild, non-aggressive solvent

APPLICATION

Recommended for:

Auxiliary product for parts refinishing and spot repair

Substrate:

- surfaces from metal, plastics, glass
- which have been filled and primed;
- old paint coats,
- coated and uncoated surfaces

APPLICATION

Protections:



Personal protection is required
Respirator mask type: A2/P2



Protective gloves,
e.g. from latex or nitrile


Spray passes:



1 light spray pass. Wipe off again with a clean, dry cloth, allow cleaned area to dry well. Repeat process if required

Technical Information

Finish:



When work is finished, reverse aerosol and spray valve empty.

Disposal:

The emptied aerosols are suitable for household collection.

CHARACTERISTICS.

Basis of raw material: Combination of specific solvents

VOC value: 620 g/l 248 g/aerosol

Solid content: n/a

Degree: of gloss n/a

Shelf life: 36 months

The description of the shelf life refers to an unused can being stored appropriately at a temperature of 15 to 25 °C and a relative humidity beneath 60%. Keep the can dry. It should stored and transported uprightly being protected from chemical and mechanical impacts. The safety instructions on the label and all legal regulations concerning the storage location have to be observed.

Remarks: For professional use only

The information contained in this paper corresponds to our present knowledge and is a guide to our products and their uses. It is not to be understood as a guarantee for certain properties of our products or of their specific applications. The warnings printed on our labels must be respected. Any industrial property rights should be observed.