



Technical Sheet:
Sverniciatore E 92 New

Code:
1220

Sigla: ST220
Rev.: 23
Date: 14/07/21

Product Type:
Dichloromethane free Paint remover.

Formats:
Cans: 20 - 4 - 0,750 liters.
Drums: 170 liters

Product Characteristics:

Product based on organic solvents free of Dichloromethane, based on the provisions of regulation (EU) no. 276/2010 amending REACH Regulation.

Technical Specifications of the Product:

CHARACTERISTICS	UM	VALUE	METHOD	TOLERANCE
Physical Aspect		Pasty	Visual	//
Color		Blue	Visual	//
Density at 20°C	Kg/dm ³	0,930	Met. Int. ISTR. 44	± 0,02

Yield: 2 m²/l aprox.
(This value is indicative as it depends on the application, type and thickness of the paint, the characteristics of the surfaces and the environmental temperatures)

Action Time:
10-20 minutes for synthetic paints.
30-60 minutes for polyurethane paints.
4-10 hours for polyester paints, epoxy and oven-cured enamels.

Use / Applications:

The product is effective on synthetic paints even with several layers, oil paints, nitrocellulose, acrylic, polyesters, two-component polyurethane, cold and oven enamels, water-based paints and plastics, fillers, adhesives for carpets and parquet.

Also indicated in the nautical sector, furniture restoration, construction and stone application.

How to use:

Mix the product after opening the container.

Apply a generous layer of paint remover with brush or a spatula. Wait for the product to penetrate completely, then remove everything with a spatula or a rag.

It has a density that allows a perfect spreading even on vertical surfaces and the coloring facilitates a homogeneous application.

Warning:

For applications on tough paints and with long action times, it is advisable to apply a cellophane film over the product, especially on hot weather conditions.

Avoid use on plastics, hot surfaces or exposed to the sunlight.

In the case of use on wood, being a natural and variable support, it is advisable to carry out an application test, in a small area that is not very visible, to avoid undesired effects.

Product not suitable for use in the body shop.

Do not shake before use. Open the cap carefully, as the product could discharge violently if under pressure; then cover the mouthpiece with a rag and pull the opening ring slowly, until it is vented, keeping the container away from the face.

Wear protective goggles and gloves during application.

keep the container tightly closed, away from any heat source and in a cool and dry place.

The waste produced by the use of the remover should always be considered as hazardous and disposed of through specialized companies.

The above information is given according to our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the Fidea SpA control.